

CAMERA SYSTEM COMPACT PROFESSIONAL KA0004



CONTENT

- camera compact professional stainless steel
- 7" monitor professional 2.0
- monitor cable for the input of 3 cameras
- 20m connector cable
- base
- remote control



ADVANTAGE: SMALL COMPACT CAMERA



7" MONITOR PROFESSIONAL 2.0

- 7" screen diagonal (approx. 18cm)
- display resolution 1.024 x 600 pixels
- 3 camera inputs for an image display on 3 channels
- monitor turns on automatically when you go into reverse
- incl. monitor holder
- guides connectable



CAMERA COMPACT PROFESSIONAL

- 1/3 CMOS colour sensor
- viewing angle 110° H / 95° V / 145° D
- dimension: 40 x 35 x 36mm
- -40°C to +85°C
- resolution 700 TV lines
- automatic backlight compensation
- automatic white balance
- built-in heating
- protection class IP69k
- shock- and vibration proof aluminium-pressure casting housing with stainless steel sunshine roof and base



20M CABLE 5PIN.

- length: 20m
- both-sided round plug 5pin. DIN-standard
- protection class IP68, protected against saltwater

KA002101



TRAILER CABLE (OPTIONAL)

- for R7-s (shutter reverse driving system)
- 5pin.