

Kamerasystem R7-S Compact Shutter KA101049

Inhalt:

- 7" Farb TFT-Monitor
- Kamera Compact Edelstahl Infrarot mit Shutter
- 20 Meter Anschlusskabel
- Monitorkabel
- Montagematerial
- Standfuß
- Fernbedienung



7" FARB TFT MONITOR

- Ultraflacher Farb-TFT-Monitor
- 7 Zoll Bildschirmdiagonale (ca. 18 cm)
- Auflösung 800 x 480 Pixel
- Abstandslinien zuschaltbar
- Spiegelfunktion horizontal und vertikal möglich
- Bei Anschluss an den Rückwärtsgang automatisches Einschalten des Monitors
- bis zu 2 Kameras anschließbar
- 182 x 122 x 26 mm (B x H x T)



KAMERA R7-S COMPACT SHUTTER

- Blickwinkel von 150°
- IR-LEDs für eine leistungsstarke Nachtsichtfähigkeit
- Integrierte Heizung
- Autom. Weißabgleich und Gegenlichtkompensation
- 12-32V DC
- -30°C bis +70°C
- Wasserdicht IP69k
- Einblendbare Hilfslinien
- (B x H x T) 80 x 65 x 60 mm



20M KABEL 5-PIN

- Länge: 20 Meter
- Beidseitiger Rundstecker 5 Pin, verschraubbar
- Wasserdicht nach Schutzklasse IP68

Camera set R7-S Compact Shutter KA101049

Content:

- 7 "color TFT monitor
- Camera Compact stainless steel infrared with shutter
- 20 meter connection cable
- Monitor cable
- Mounting material
- Stand
- Remote control



7 "COLOR TFT MONITOR



- Ultra-flat color TFT monitor
- 7 inch screen diagonal (approx. 18 cm)
- Resolution 800 x 480 pixels
- Distance lines can be activated
- Horizontal and vertical mirror function possible
- When connected to reverse gear, the monitor switches on automatically
- Up to 2 cameras can be connected
- 182 x 122 x 26 mm (W x H x D)

CAMERA R7-S COMPACT SHUTTER



- Angle of view of 150 °
- IR LEDs for powerful night vision capability
- Integrated heating
- Auto white balance and backlight compensation
- 12-32V DC
- -30 ° C to + 70 ° C
- Waterproof IP69k
- Guide lines that can be shown
- (W x H x D) 80 x 65 x 60 mm

20M CABLE 5-PIN



- Length: 20 meters
- Circular screwable 5 pin connector on both sides
- Waterproof according to protection class IP68