

Kamerasystem R7-S Shutter KA300501



Inhalt:

- 7" Farb TFT-Monitor
- Kamera Infrarot mit Shutter
- 20 Meter Anschlusskabel
- Monitorkabel
- Montagematerial
- Standfuß
- Fernbedienung



7" FARB TFT MONITOR



- Ultraflacher Farb-TFT-Monitor
- 7 Zoll Bildschirmdiagonale (ca. 18 cm)
- Auflösung 800 x 480 Pixel
- Abstandslinien zuschaltbar
- Spiegelfunktion horizontal und vertikal möglich
- Bei Anschluss an den Rückwärtsgang automatisches Einschalten des Monitors
- bis zu 2 Kameras anschließbar
- 182 x 122 x 26 mm (B x H x T)

offen



geschlossen



KAMERA R7-S SHUTTER

- Infrarot Kamera
- 1/4 Sharp CCD-Farbsensor
- Blickwinkel: 110° H / 80° V / 135° D
- Autom. Gegenlichtkompensation und Weißausgleich
- 4 x IR LEDs für eine Top-Nachtsichtfähigkeit bis 15 m
- -30°C bis +70°C
- Schutzklasse IP69k
- Aluminium-Druckgussgehäuse
- Elektroschutter-Abdeckung
- Maße (L x B x H) 120 x 86 x 79 mm

20M KABEL 5-PIN



- Länge: 20 Meter
- Beidseitiger Rundstecker 5 Pin, verschraubbar
- Wasserdicht nach Schutzklasse IP68

Camera system R7-S Shutter KA300501



Inhalt:

- 7 "color TFT monitor
- Camera infrared with shutter
- 20 meter connection cable
- Monitor cable
- Mounting material
- Stand
- Remote control



7 "COLOR TFT MONITOR



- Ultra-flat color TFT monitor
- 7 inch screen diagonal (approx. 18 cm)
- Resolution 800 x 480 pixels
- Distance lines can be activated
- Horizontal and vertical mirror function possible
- When connected to reverse gear, the monitor switches on automatically
- Up to 2 cameras can be connected
- 182 x 122 x 26 mm (W x H x D)

open



closed



CAMERA R7-S SHUTTER

- Infrared camera
- 1/4 Sharp CCD color sensor
- Viewing angle: 110 ° H / 80 ° V / 135 ° D
- Auto backlight compensation and white balance
- 4 x IR LEDs for top night vision up to 15 m
- -30 ° C to + 70 ° C
- Protection class IP69k
- Die-cast aluminum housing
- Electric shutter cover
- Dimensions (L x W x H) 120 x 86 x 79 mm

20M CABLE 5-PIN



- Length: 20 meters
- Circular screwable 5 pin connector on both sides
- Waterproof according to protection class IP68